



XP-T12K-UK-ALIZE

Product advantages

- Full control panel
- electric start
- long life' engine
- Very large autonomy
- Very Silent

Zoom

AVR

This ensures that the voltage output from the generator set remains within +/- 2% of the rated voltage. By comparison, a generator set without such a device generally runs at +/- 10 % of its rated voltage.

The Mics NEXYS control panel displays the frequency, battery voltage, timer, hours counter and genset speed.

Miscellaneous

The top quality alliance of performance and soundproofing.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

XP-T12K-UK-ALIZE

General specifications

Range	Industrial
Frequency (Hz)	50
Max. power (kW)	9.20
Max power. (kVA)	11.50
Nominal voltage (V)	400
Number of phase	Three phase - 400 V
Acoustic pressure level Lw	86
Noise level dB(A) - 7m	60

Engine specifications

Engine trademark	Mitsubishi
Engine type	S3L2 SD
Distribution	Fuel 1500
Start	Electrical
Fuel	Fuel
Autonomy (h)	20
Consumption (L/h)	2.5
Tank (L)	50
Oil Guard	Yes
Capacity (cm3)	1318
Oil capacity (L)	3.7

Alternator specifications

Type	With collar and brush
Regulation	Electronic
Protection class	IP 23
Insulation class	H

Plugs and panels descriptive

1 x 2P+T 115V 16A - circuit breaker + 1 x 2P+T 230V 16A - circuit breaker + 1 x 3P+T+N 400V 16A - circuit breaker + Mics NEXYS

Dimensions and weight

Length (cm)	175
Width (cm)	77.5
Height (cm)	123
Dry Weight (kgs)	535

Packaging

Packaging type	Canopy + Film
Length (cm)	175
Width (cm)	77.5
Height (cm)	123

