



XP-T6KM-UK-ALIZE

Product advantages


- Full control panel
- electric start
- long life' engine
- Very large autonomy
- Very Silent

Zoom

The Mics NEXYS control panel displays the frequency, battery voltage, timer, hours counter and genset speed.

Miscellaneous

The top quality alliance of performance and soundproofing.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

XP-T6KM-UK-ALIZE

General specifications

Range	Industrial
Frequency (Hz)	50
Max. power (kW)	5.50
Max power. (kVA)	6.00
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Acoustic pressure level Lw	86
Noise level dB(A) - 7m	59

Engine specifications

Engine trademark	Mitsubishi
Engine type	L3E SD
Distribution	O.H.V.
Start	Electrical
Fuel	Fuel
Autonomy (h)	29.4
Consumption (L/h)	1.7
Tank (L)	50
Oil Guard	Yes
Capacity (cm3)	952
Oil capacity (L)	3.6

Alternator specifications

Type	With collar and brush
Regulation	Electronic
Protection class	IP 23
Insulation class	H

Plugs and panels descriptive

1 x 2P+T 115V 16A - circuit breaker + 1 x 2P+T 230V 16A - circuit breaker + 1 x 2P+T 230V 32A - circuit breaker + Mics NEXYS

Dimensions and weight

Length (cm)	150
Width (cm)	76
Height (cm)	103
Dry Weight (kgs)	390

Packaging

Packaging type	Canopy + Film
Length (cm)	150
Width (cm)	76
Height (cm)	103

Delivered accessories
Options

	R50	Male Plug R50	16A blue 230V male plug - Sold per 1 or 10
	R51	Male Plug 115V/16A	16A yellow 115V male plug - Sold per 1 or 10
	R54	Adaptator unit 16A/13A	Adaptator R54 16A/13A adaptator unit. Sold per 1 or 3
	R55	Adaptator economy 13A/16A	ADAPTATOR R55 16A/13A adaptator economy. Sold per 1 or 3
	R56	Double adaptator 16A/13A	ADAPTATOR R56 16A/13A double adaptator. Sold per 1 or 3
	RBH1	Box of 20 1L cans of oil	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
	RBH0-5	Container of oil RBH0,5	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
	R04	Remote control R04	Remote control unit with, on indicator and generator fault. Delivered without cables.
	RPQ	Earth spike	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm ² cable.
	R05B	Automatic start mains failure panel	Automatic start (including engine preheating control, charger, Normal/Backup inverter).
	530050	Road trailer 530050	UK road trailer - Details upon request

