

## T25C2M - Generating set

T25C2M Power Products Generating set, equipped with a MITSUBISHI engine and MECC ALTE alternator.

### General characteristics


Mechanic governor
Mechanically welded chassis with antivibration suspension
Main line circuit breaker
Radiator for wiring temperature of 48/50°C max with mechanical fan
Protective grille for fan and rotating parts
9 dB(A) silencer supplied separately
Charger DC starting battery with electrolyte
12 V charge alternator and starter
Delivered with oil and coolant -30°C
Manual for use and installation



Voltage (V)	ESP Power (kWe/kVA)	PRP Power (kWe/kVA)	Back-up power (A)	Dimensions (L. x l. x h.)	Weight
240 MONO	25/25	25/25	104	Length : 1700 mm Width : 896 mm Height : 1144 mm	710 kg net
230 MONO	25/25	25/25	108		820 kg gross
220 MONO	25/25	25/25	113		

## Hoods

---

	Model	dB(A)@1m	dB(A)@7m	Dimensions (L. x l. x h.)	Weight	Tank
	M127	74	74	<b>Length :</b> 2080mm <b>Width :</b> 960mm <b>Height :</b> 1415mm	940 kg net 1050 kg gross	100 L

### Standard Control Panel

### NEXYS



The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

**Standard electrical measurements:** voltmeter, frequency meter, ammeter.

**Engine parameters:** working hours counter, engine speed, battery voltage, fuel level.

**Alarms and faults:** oil pressure, coolant temperature, failure to start, overspeed (> 60 kVA), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

### Optional control panel

### TELYS



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

**Electrical measurements:** voltmeter, frequency meter, ammeter.

**Engine parameters:** working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

**Alarms and faults:** oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

**Ergonomics:** wheel for navigating around the various menus.

**Communication:** remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.